

Equipment variants and technical details.



Front mowers with pendulum support F-series

Front mower with alpine pendulum frame

Front mowers with 3D drawbar

Rear mower with side suspension (ISL)

Rear mower with side suspension

		Slicer 310 F	Slicer 310 F KC	Slicer 310 F RC	Slicer 260 FP	Slicer 260 FPS	Slicer 310 FPK		Slicer 310 FQ	Slicer 310 FQ KC	Slicer 310 FQ RC	Slicer 360 FQ	Slicer 360 FQ KC	Slicer 360 FQ RC	Slicer 2460 ISL	Slicer 2870 ISL	Slicer 270 P	Slicer 320 P	Slicer 350 P
Weights and dimensions																			
Working width	m	3,10	3,10	3,10	2,50	2,50	3,00		3,10	3,10	3,10	3,60	3,60	3,60	2,42	2,82	2,55	3,00	3,50
Transport width	m	3,00	3,00	3,00	2,50	2,50	3,00		2,99	2,99	2,99	3,49	3,49	3,49	1,80	1,80	2,13	2,13	2,13
Swath width	m	1,80	1,20 - 2,00	1,20 - 2,00	1,35	1,35	2,00		1,80	1,20 - 2,00	1,20 - 2,00	2,30	1,70 - 2,50	1,70 - 2,50	1,65	2,00	2,00	2,20	2,60
Transport height	m								1,88	1,88	1,88	1,88	1,88	1,88	3,30	3,70	2,95	3,43	3,91
Transport length	m	1,65	1,74	1,74	1,21	1,21	1,20		2,05	2,05	2,05	2,05	2,05	2,05	1,35	1,35	1,30	1,30	1,30
Weight	kg	710	1015	1045	474	504	694		950	1238	1238	1020	1343	1374	510	550	690	753	833
Power requirement																			
Power requirement	kW/HP	44/60	55/75	52/70	28/38	28/38	55/75		44/60	56/75	52/70	52/70	67/90	63/85	37/50	44/60	40/54	45/61	50/68
Hitching																			
Three-point	category	II	II	II	II	II	II		II	II	II	II	II	II	I + II	I + II	II	II	II
Cutting unit																			
Cutting discs	number	6	6	6	4	4	6		6	6	6	7	7	7	6	7	5	6	7
Blades per mower disc	number	2	2	2	2	2	2		2	2	2	2	2	2	2	2	2	2	2
Quick-release blade system		■	■	■			■		■	■	■	■	■	■	■	■	■	■	■
Compact angle drive					■	■	■										■	■	■
Front wheel drive		■	■	■					■	■	■	■	■	■	■	■			
DriveGuard							■										■	■	■
Mechanical lateral displacement																			
Hydraulic lateral displacement						■			□	□	□	□	□	□					
Hydraulic opening/closing of side guard		□	□	□					□	□	□	□	□	□					
TurboLift mowing attachment relief									■	■	■	■	■	■					
ISOBUS control																			
SafetySwing																			
BeMove																			
RC DUO drive				□							□			□					
Hydraulics																			
Required sa hydraulic connections	number								1	1	1	1	1	1	1	1	1	1	1
Required da hydraulic connections	number					1													
Flat face coupling									□	□	□	□	□	□					
PTO																			
PTO speed	rpm	1000 (850)	1000 (850)	1000 (850)	540/1000	540/1000	1000		1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	540	540	540	540	540
Drive shaft with freewheel					■	■	■								■	■	■	■	■
Free wheel in the gearbox		■	■	■					■	■	■	■	■	■					
Lighting																			
Electrical lighting / warning signs		□	□	□			□		□	□	□	□	□	□			□	□	□

